

1815 Hood Light Fixture

Part Number: 11815000010

⚠ CAUTION/ATENCIÓN

High Surface Temperatures: Install only where the fixture is no mounted on a or adjacent to combustible materials

Surfaces très chaudes: Nes pas installer cet appariel d'éclairage a proximite d'une surfaceible in sur cette derniere

DIRECTIONS

1. Disconnect all power to the supply leads
2. Cut hole in hood in the pattern shown
3. Remove display lens and reflector
4. Install supplied 1/2" conduit fitting in desired knockout
5. Position housing gasket onto housing mounting studs
6. Insert the fixture into hole and install with #10-24 mounting nuts (supplied by others)
7. Make all electrical connections **Note:** All supply wires to be suitable for 90°C. All wiring must comply with the national electric code
8. Install reflector and safety strap
9. Install display lens

Fixture is to be installed NO less than 4 feet (1.2M) above cooking surface.

Install with minimum spacings between:

- Center-to-center of adjacent luminaries: 610mm (24in)
- Top of luminaire to overhead member: 305mm (12in)
- Luminaire center to side building member: 152mm (6in)

SPECIFICATIONS

- Watertight - Etanche
- Input Volts: 100 - 277 VAC
- Frequency: 50/60 Hz

