## **PRODUCT UPDATE**



## 0057E SecureGuard<sup>™</sup> Security Latch with Electronic Flush Strike

Part Number: 10057E\*





Interior View

## MATERIALS

- Base Plate: Steel
- **Top Cover:** Optional 300 series stainless steel or powder coated steel
- Strike Spacer: Gray ABS
- Mounting Plates: Anodized aluminum
- Latch Body Cover: Stainless Steel
- Latch Tongue: Zamak #3
- Pull Handle: Zamak #3, polished chrome plated
- Push Handle: Stainless steel
- Couplings: Plastic
- Hardware: Stainless steel
- Electric Strike Assa Abloy 9600: Stainless steel
- Card Reader HID: See table for model number

Part No.*	Description	Wgt./ Carton
100 <i>57</i> E00008	Latch with Electronic Strike, Flush, SFIC 7-pin Removeable Core Cylinder	16.4 lb (7.4 kg)
100 <i>57</i> EK0008	Latch with Electronic Strike, Flush, SFIC 7-pin Removeable Core Cylinder, Quick Release Knob	16.6 lb (7.5 kg)
900 <i>57</i> E00250	E-strike Assembly	6.5 lb (2.9 kg)
90058E00220†	HID Card Reader 920NTNNEK0, Model R40E	0.54 lb (0.24 kg)
<sup>†</sup> Sold separately		



Exterior View

The Kason 0057E Security Latch is the newest line of defense in securing your walk-in contents. It easily integrates with your existing security system to meet your access and control needs. This unique solution utilizes Kason mechanical latches and inside release systems designed specifically for walk-in applications.

- Add access control and security to your walk-in
- Integrates with existing security systems
- Utilizes high-security industry standard UL Certified electronic strike latch
- Strike located inside room for increased tamper resistance
- Electric strike can be set to either Fail Safe or Fail Secure
- Physical key override allows entry with power off and fail secure setting
- Accepts user specified card readers intended for standard junction box mounting
- Durable, low-maintenance construction
- Quick Release Knob option offers a quick, key-free lock override for easier access during high-traffic times
- Temperature Range: -20°F to 120°F (-29°C to 49°C)

kasonind.com | 1.800.935.2766