

0488L Panic Bar Inside Release and Latch Assembly (UL 305 Certified)

Part Number: 10488L*



U.S. Patent No. 11,193,311



MATERIALS

- **Cross bar:** 304 stainless steel
- **Mounting brackets:** 304 stainless steel
- **Push rod:** 303 series stainless steel
- **Cover:** Die-cast aluminum
- **Pivot arm:** Die-cast aluminum
- **Hardware:** Stainless steel
- **Pin:** 304 stainless steel
- **Springs:** Music wire
- **End caps:** Black polyethylene
- **Bearings:** Bronze

The Kason 0488L panic bar is specifically designed for generator enclosures and/or acoustic chamber door applications that utilize Kason mechanical latches on their exteriors.

- **UL305 and Can/ULC-S132 certified panic device**
- **Stainless steel and aluminum construction**
- **Crossbar provides a large contact area for opening door**
- **Ergonomic design provides simple low-effort operation**
- **Accommodates left/right handed doors**
- **Temp. range: -40°F to 150°F (-40°C to 65°C)**
- **Includes Kason 0778 latch and 0778 or 0779 strike**



Visit kasonind.com for information on the [0778](#) latch and [0779](#) strike options

Part No.*	Description	Door Thickness	Weight
10488LC225102	Panic Bar Inside Release w/ 0778 Latch and 0778 Flush Strike, 2-1/4" Wall #602 (UL)	2-1/4" (57.2 mm)	11.59 lb (5.26 kg)
10488LC225302	Panic Bar Inside Release w/ 0778 Latch and 0779 Flush Strike, 2-1/4" Wall #602 (UL)	2-1/4" (57.2 mm)	11.76 lb (5.33 kg)
10488LC400102	Panic Bar Inside Release w/ 0778 Latch and Strike, 4" Wall #602 (UL)	4" (101.6 mm)	11.59 lb (5.26 kg)
10488LC400302	Panic Bar Inside Release w/ 0778 Latch and 0779 Flush Strike, 4" Wall #602 (UL)	4" (101.6 mm)	11.76 lb (5.33 kg)