

0488L Panic Bar Inside Release and Latch Assembly (UL 305 Certified)

Part Number: 10488L*

FEATURES

- UL305 and Can/ULC-S132 certified panic device
- Stainless steel and aluminum materials for non-corroding construction
- Crossbar design provides a large contact area for opening door
- Ergonomic design provides simple low-effort operation
- Accommodates left and right handed doors

MATERIALS

- **Cross bar:** 304 stainless steel
- **Mounting brackets:** 304 stainless steel
- **Push rod:** 303 series stainless steel
- **Cover:** Die-cast aluminum
- **Pivot arm:** Die-cast aluminum
- **Hardware:** Stainless steel
- **Pin:** 304 stainless steel
- **Springs:** Music wire
- **End caps:** Black polyethylene
- **Bearings:** Bronze



U.S. Patent No. 11,193,311



Visit kasonind.com for information on the [0778](#) latch and [0779](#) strike options

DESIGN CRITERIA

- **Temp range:** -40°F to 150°F (-40°C to 65°C)
- Tested to UL305 & Can/ULC-S132 standard for panic devices
- Certified for doors up to 4' x 7' (width x height)
- Models available for flush through 1-5/8" offset doors
- Designed for 1/4" mounting screws

| Part No.* | Description | Door Thickness | Qty./Carton | Wgt./Carton |
|---------------|---|------------------------------------|-------------|--------------------|
| 10488LC200102 | Panic Bar Inside Release w/ 0778 Latch and 0779 Strike, #602 (UL) | 2" to 2-1/4 (50.8 to 57.2 mm) | 1 | 12 lb (5.44 kg) |
| 10488LC200302 | Panic Bar Inside Release w/ 0778 Latch and Strike, #602 (UL) | 2" to 2-1/4 (50.8 to 57.2 mm) | 1 | 12.18 lb (5.52 kg) |
| 10488LC225102 | Panic Bar Inside Release w/ 0778 Latch and 0778 Flush Strike, #602 (UL) | 2-1/4" to 2-1/2" (57.2 to 63.5 mm) | 1 | 12.36 lb (5.6 kg) |
| 10488LC225302 | Panic Bar Inside Release w/ 0778 Latch and 0779 Flush Strike, #602 (UL) | 2-1/4" (57.2 mm) | 1 | 12.52 lb (5.68 kg) |
| 10488LC400102 | Panic Bar Inside Release w/ 0778 Latch and Strike, #602 (UL) | 4" (101.6 mm) | 1 | 12.47 lb (5.66 kg) |
| 10488LC400302 | Panic Bar Inside Release w/ 0778 Latch and 0779 Strike, #602 (UL) | 4" (101.6 mm) | 1 | 12.64 lb (5.73 kg) |
| 10488LC425102 | Panic Bar Inside Release w/ 0778 Latch and Strike, #602 (UL) | 4-1/4" to 4-1/2" (108 to 114.3 mm) | 1 | 12.15 lb (5.51 kg) |

| Part No.* | Description |
|----------------|---|
| 90778CX6020 | Latch for 0488L, Light Spring |
| 90778X00130 | Strike Insert Assembly, Flush, Brass Roller |
| 90778X00131 | Strike Insert Assembly, 3/4" to 1-1/2", Brass Roller |
| 90778X06020 | Latch for 0488L, Light Spring, Padlocking |
| 90778X06202 | Strike Assembly, 1/8" to 3/4", Brass Roller, Satin |
| 90778X06203 | Strike Assembly, 3/4" to 1-5/8", Brass Roller, Satin |
| 90488CS1115630 | Push Rod 5.63" for Standard 0488C, 2-1/4 to 2-1/2" Door, Stainless Steel |
| 90488CS1117460 | Push Rod 7.46" for Standard 0488C, 4" Door, Stainless Steel |
| 90488CS1117630 | Push Rod 7.63" for Standard 0488C, 4-1/4" to 4-1/2" Door, Stainless Steel |



0488L Panic Bar Inside Release and Latch Assembly (UL 305 Certified)

Part Number: 10488L*

